

MAT'LS:

WOOD: 2X4, 2X6, 2X8 (AS REQUIRED)

#8 DRYWALL SCREWS,
STAPLES, PADDING MAT'L,
WIRE TIES

ATTACH/
STAPLE
PADDING:
CARPET, HEAVY CLOTH,
FOAM, RUBBER, ETC.

WASHER FOR HOOKING
TIE DOWNS AROUND CYCLE
(PULL BIKE AGAINST STA-BAR)

BLOCK OF WOOD
SCREWED TO STA-BAR
(CONTOUR TO MOUNT AREA)
I.E. FRAME, SIDE PLATE,
SEAT, ETC

INSIDE
VERTICAL
STABILIZER
BAR

-WRAP W/PADDING
IF CYCLE MAY
COME INTO
CONTACT

SECURING VERT STA-
BAR TO CARRIER B'KT:

VERY TIGHT - 65 FT-LBS JAMB
(AFTER SNUG BOLT)

1/2-13
HHCS
GRADE 5
MIN.

SNUG IN
RAISED
POSITION

TOOLS REQ'D:
DRILL W/ 1/8" ϕ BITS,
CROSSCUT SAW, STAPLER, FILE
3/4" BOXED END WRENCH,
3/4" SOCKET W/ RATCHET

USE
OUTSIDE
STA-BAR
FOR CYCLES
OVER 500 LBS

SAS LLC 09-07

VERTICAL STA-BAR NOTES

CUSTOMIZATION/MOUNTING INSTRUCTIONS

WWW.MOTORCYCLERACKS.NET / WWW.CARRIERSACYCLES.COM

